

Amendments

In the Claims:

Please cancel claims 1-34 without prejudice or disclaimer of the subject matter therein. This listing of claims will replace all prior versions, and listings of claims in the application. Currently amended claims are shown with additions underlined and deletions in ~~striketrough~~ text. No new matter is added by these amendments.

Listing of the Claims:

Claims 1-34 (Canceled)

35. (Previously Presented) A tray insert removably disposable within a cavity of a support, the support including a rim and a lower surface defining the cavity, said tray insert comprising:

4B1 a body portion including a first surface having a plurality of pockets formed therein and a second surface adapted to rest against said lower surface of the support; and

a coupling member disposed on said body portion, said coupling member adapted to releasably engage the support within the cavity of the support.

36. (Previously Presented) The tray insert of claim 35, wherein said coupling member is adapted to releasably engage a recess formed in the support.

37. (Previously Presented) The tray insert of claim 36, wherein said coupling member includes a protrusion having an inclined surface, said coupling member adapted to mechanically engage the recess.

38. (Previously Presented) The tray insert of claim 37, wherein said coupling member is disposed on said second surface.

39. (Previously Presented) The tray insert of claim 36, wherein said body portion includes an extending portion configured to conform to and engage a portion of the support rim.

UP!
cont

40. (Previously Presented) The tray insert of claim 39, wherein said extending portion has a U-shaped configuration.

41. (Previously Presented) A tray set comprising:
a support having a cavity formed therein, said cavity being defined by a rim and a support surface within said rim, said rim further defining a perimeter of said support and having a first configuration; and

a liner disposable within said cavity and contacting substantially all of said support surface, said liner having an outer portion releasably engagable with said rim of said support, said outer portion having a second configuration, said first configuration being substantially the same as said second configuration.

42. (Previously Presented) The tray set of claim 41, wherein said liner includes a body portion and a coupler disposed on said body portion, said coupler positively engaging said support such that said liner is releasably engageable with said support.

43. (Previously Presented) The tray set of claim 42, wherein said support includes a recess formed in said rim, said coupler engaging said recess and coupling said liner to said support.

44. (Previously Presented) The tray set of claim 42, wherein said rim includes an inner surface and an outer surface, said support includes a recess formed in said outer surface, said liner includes an upper surface and a lower surface, said coupler disposed on said lower surface, said coupler engaging said recess and coupling said liner to said support.

45. (Previously Presented) The tray set of claim 41, wherein said support includes a coupler disposed on said rim, said coupler positively engaging said liner such that said liner is releasably engageable with said support.

46. (Previously Presented) The tray set of claim 45, wherein said rim includes an inner surface and an outer surface, said coupler being disposed on said inner surface, said liner includes an upper surface, a lower surface, and a recess formed in said lower surface, said coupler engaging said recess to couple said liner and said support together.

47. (Previously Presented) The tray set of claim 41, wherein said support includes a plurality of recesses formed in said rim, said plurality of recesses extending below an upper surface of said liner.

48. (Previously Presented) A tray kit comprising:

*UBI
can't*

a first tray having a body portion and a perimeter portion extending around said body portion, said body portion having a plurality of pockets formed therein, said perimeter portion including a latch disposed on a lower surface thereof; and

a second tray, said second tray having an upper surface with a cavity formed therein and defined by a rim extending around said cavity, said rim including a recess formed therein, said latch of said first tray being selectively coupleable with said recess to retain said first tray in said cavity.
